

A9C32836

produžetak ETL iTL 32–1P –1NO–32 A–zavojnica
110 V DC–230...240 V AC 50/60 Hz



Glavno

Range	Acti 9
Product or component type	Extension for impulse relay
Device short name	IETL iTL 32
Relay application	Remote control
Poles description	1P
Pole contact composition	1 NO
[In] rated current	32 A
Network type	AC

Komplementarno

Network frequency	50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
Control type	Remote control Toggle
Control signal type	Impulse
Switching frequency	5 switching operations/minute
Impulse duration	50 ms
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
[Uc] control circuit voltage	110 V DC 230...240 V AC 50/60 Hz
Supply inrush power	19 VA
Mounting mode	Fixed, on right side of TL
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	60 mm
Width	18 mm
Depth	84 mm
Colour	White
Electrical durability	AC-21: 50000 cycles AC-22: 20000 cycles
Connections - terminals	Tunnel type terminals <= 10 mm ²
Range compatibility	Acti 9 iTL
Product compatibility	ITL 32A

Okolina

standards	EN 669-1 EN 669-2-2
noise level	<= 60 dB
IP degree of protection	IP20 conforming to IEC 60529
pollution degree	3
tropicalisation	2 conforming to IEC 60068-1
relative humidity	95 % (55 °C)
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-40...70 °C

Informacije dane u ovoj dokumentaciji sadrže opće tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1825 - Schneider Electric declaration of conformity	Compliant - since 1825 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------