



Glavno

| | |
|---------------------------|------------------------------------|
| Device application | Control Distribution |
| Range | Acti 9 |
| Product name | Reflex iC60 |
| Device short name | Reflex iC60N |
| Product or component type | Integrated control circuit breaker |
| Poles description | 2P |
| Number of protected poles | 2 |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | B |

Komplementarno

| | |
|-------------------------------|--|
| [In] rated current | 63 A |
| Network frequency | 50/60 Hz |
| Breaking capacity code | N |
| Breaking capacity | Icu 20 kA at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 Icu 10 kA at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| [Ui] rated insulation voltage | 500 V AC |
| Contact position indicator | Yes |
| Control type | Remote control by continuous command Remote control by pulse Toggle ON/OFF button |
| Control signal type | Impulse Maintained Maintained very low voltage |
| Local signalling | Red LED: fault Flashing LED: device overheat Flashing LED: device ready Flashing LED: device tripped Green LED: device ON |
| [Uc] control circuit voltage | 230 V AC 50/60 Hz 24 V AC 50/60 Hz 24 V DC 48 V AC 50/60 Hz 48 V DC |
| [Us] rated supply voltage | 230 V AC 50/60 Hz |
| Mounting mode | Fixed |
| Mounting support | 35 mm symmetrical DIN rail |
| 9 mm pitches | 9 |
| Height | 84 mm |
| Width | 81 mm |
| Depth | 77 mm |
| Colour | White |
| Mechanical durability | 50000 cycles |
| Electrical durability | AC-1: 50000 cycles AC 50 Hz |
| Provision for padlocking | Padlockable |
| Locking options description | Padlock in OFF position |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|--------------------------|----------------|
| Earth-leakage protection | Separate block |
| Product compatibility | With PLC |

Okolina

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP20 conforming to IEC 60529 |
| pollution degree | 3 |
| tropicalisation | 2 |
| relative humidity | 93 % (40 °C) |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1329 - Schneider Electric declaration of conformity | Compliant - since 1329 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Available | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|