



Glavno

Range	Acti 9
Product or component type	Remote control auxiliary
Device short name	RCA iC60
Signal contacts composition	1 OF volt-free contacts
Signalling circuit voltage	Volt-free contact 24...230 V 0.01...1 A AC

Komplementarno

Control type	Remote control impulse and maintained 230 V AC 50/60 Hz
Input current	5 mA impulse 5 mA maintained
Impulse duration	>= 200 ms control circuit
Response time	< 500 ms
[Us] rated supply voltage	230 V AC 50/60 Hz
Power consumption in W	1 W
[Ui] rated insulation voltage	400 V
[Uimp] rated impulse withstand voltage	6 kV
Value of setting	Mode A : reclosing authorized after tripping Mode B : reclosing inhibited after tripping Auto : remote control authorized Off : remote control inhibited
Local signalling	Flashing orange LED: not operational Flashing green LED: ready to operate
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	NO
9 mm pitches	7
Height	93 mm
Width	63 mm
Depth	75.5 mm
Product weight	400 g
Colour	White
Electrical durability	10000 cycles
Mechanical durability	10000 cycles
Provision for padlocking	Padlockable
Wire stripping length	Power supply: 10 mm (bottom) Input: 10 mm (bottom) Output: 8 mm (top)
Tightening torque	Power supply: 1 N.m Input: 1 N.m Auxiliary output: 0.7 N.m
Range compatibility	Acti 9: Acti 9 iC65 Acti 9: Acti 9 iC60 Acti 9: iMDU voltage adaptor
Product compatibility	IC60 2P IC60 1P + N iMDU

Okolina

IP degree of protection	IP20 conforming to IEC 60529 IP40 (in modular enclosure) conforming to IEC 60529
pollution degree	3 conforming to IEC 60947
overvoltage category	II
tropicalisation	2
relative humidity	93 % at 40 °C
ambient air temperature for storage	-40...70 °C
ambient air temperature for operation	-25...60 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1312 - Schneider Electric declaration of conformity	Compliant - since 1312 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------