



Glavno

Range	Acti 9
Product or component type	Remote control auxiliary
Device short name	RCA iC60
Signal contacts composition	1 OF volt-free contacts
Signalling circuit voltage	Volt-free contact 24...230 V 0.01...1 A AC

Komplementarno

Control type	Remote control impulse and maintained 230 V AC 50/60 Hz
Input current	5 mA impulse 5 mA maintained
Impulse duration	>= 200 ms control circuit
Response time	< 500 ms
[Us] rated supply voltage	230 V AC 50/60 Hz
Power consumption in W	1 W
[Ui] rated insulation voltage	400 V
[Uimp] rated impulse withstand voltage	6 kV
Value of setting	Mode A : reclosing authorized after tripping Mode B : reclosing inhibited after tripping Auto : remote control authorized Off : remote control inhibited
Local signalling	Flashing orange LED: not operational Flashing green LED: ready to operate
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	NO
9 mm pitches	7
Height	93 mm
Width	63 mm
Depth	75.5 mm
Product weight	430 g
Colour	White
Electrical durability	10000 cycles
Mechanical durability	10000 cycles
Provision for padlocking	Padlockable
Wire stripping length	Power supply: 10 mm (bottom) Input: 10 mm (bottom) Output: 8 mm (top)
Tightening torque	Auxiliary output: 0.7 N.m Auxiliary supply: 1 N.m Auxiliary input: 1 N.m
Range compatibility	Acti 9: Acti 9 iC65 Acti 9: Acti 9 iC60 Acti 9: iMDU voltage adaptor
Product compatibility	IMDU IMDU IC60 3P or 4P

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanosti, poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Okolina

IP degree of protection	IP20 conforming to IEC 60529 IP40 (in modular enclosure) conforming to IEC 60529
pollution degree	3 conforming to IEC 60947
overvoltage category	II
tropicalisation	2
relative humidity	93 % at 40 °C
ambient air temperature for storage	-40...70 °C
ambient air temperature for operation	-25...60 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1312 - Schneider Electric declaration of conformity	Compliant - since 1312 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------