



Glavno

Product or component type	Cartridge
Device short name	C neutral-350
Surge arrester type	Electrical distribution network

Komplementarno

Surge arrester class type	Type 2
Surge arrester technology	GDT
Earthing system	TN TT
[Ue] rated operational voltage	230 V AC 50 Hz
Nominal discharge current	20 kA
Maximum discharge current	65 kA
[Uc] maximum continuous operating voltage	260 V
[Up] voltage protection level	1.4 kV type 2
Local signalling	Flag color: white/red
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	2
Height	57 mm
Width	18 mm
Depth	56 mm
Product weight	0.044 kg
Colour	White (RAL 9003)
Material	PBT (polybutylene terephthalate)
Response time	< 100 ns

Okolina

standards	EN 61643-11 IEC 61643-11: 2011
product certifications	CE
IP degree of protection	Front face: IP20
relative humidity	5...90 %
operating altitude	0...2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0844 - Schneider Electric declaration of conformity	Compliant - since 0844 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available