



### Glavno

Range	Acti 9
Product name	Acti 9 iPRD
Product or component type	Surge arrester with pluggable cartridge
Device short name	IPRD8r
Device application	Distribution
Poles description	3P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	IT

### Komplementarno

Surge arrester class type	Type 2 + 3
Surge arrester technology	MOV
[Ue] rated operational voltage	230/400 V (+/- 10 %) AC 50/60 Hz
Nominal discharge current	Common mode: 2.5 kA L/PE
Maximum discharge current	Common mode: 8 kA L/PE
[Uc] maximum continuous operating voltage	Common mode: 460 V L/PE
[Up] voltage protection level	1.6 kV type 2 common mode L/PE 1.8 kV type 3 common mode L/PE
[Ut] temporary overvoltage	Withstand: 337 V L/Nfor 5 s Safe failure mode: 1455 V L/PEfor 200 ms Safe failure mode: 1455 V N/PEfor 200 ms
Disconnecter device type	Associated circuit breaker iC60L 10 A curve C - Icu 25 kA
Short-circuit withstand	5 kA 415 V Ph/Ph
Local signalling	Flag color: white/red
Signalling circuit voltage	0.25 A/250 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	85 mm
Width	54 mm
Depth	69 mm
Product weight	340 g
Colour	White (RAL 9003)
Response time	<= 25 ns
Residual current	0.6 mA
Connections - terminals	Tunnel type terminal, top or bottom 2.5...25 mm <sup>2</sup> cable(s) rigid Tunnel type terminal, top or bottom 4...16 mm <sup>2</sup> cable(s) flexible Tunnel type terminal, top or bottom 4...16 mm <sup>2</sup> cable(s) flexible with ferrule
Tightening torque	3.5 N.m

### Okolina

standards	EN 61643-11: 2012 IEC 61643-11: 2011
product certifications	CE
IP degree of protection	On front face: IP40 conforming to IEC 60529 Built-in: IP20 conforming to IEC 60529
relative humidity	5...95 %

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

operating altitude	2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1640 - Schneider Electric declaration of conformity	Compliant - since 1640 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold