

A9L15692

iPF K 20 modularni odvodnik prenapona – 1 pol + N – 340 V



Glavno

Range	Acti 9
Product name	Acti 9 iPF K
Product or component type	Surge arrester
Device short name	IPF K
Device application	Distribution
Poles description	1P + N
Remote signalling	Without
Surge arrester type	Electrical distribution network
Earthing system	TN-S TT

Komplementarno

Surge arrester class type	Type 2
Surge arrester technology	MOV + GDT
[Ue] rated operational voltage	230 V (+/- 10 %) AC 50/60 Hz
Nominal discharge current	Differential mode: 5 kA L/N Common mode: 5 kA L/PE Common mode: 5 kA N/PE
Maximum discharge current	Common mode: 20 kA L/PE Common mode: 20 kA N/PE Differential mode: 20 kA L/N
[Uc] maximum continuous operating voltage	Common mode: 260 V N/PE Common mode: 340 V L/PE Differential mode: 340 V L/N
[Up] voltage protection level	1.1 kV type 2 differential mode L/N 1.5 kV type 2 common mode N/PE
[Ut] temporary overvoltage	Withstand: 337 V L/Nfor 5 s Withstand: 442 V L/PEfor 5 s Withstand: 1200 V N/PEfor 200 ms Withstand: 1453 V L/PEfor 200 ms
Disconnecter device type	Associated circuit breaker iK60N 20 A curve C - Icu 6 kA Associated fuse gG 25 A - Icu 25 kA
Short-circuit withstand	25 kA
Local signalling	LED color: green/red
Signalling circuit voltage	0.25 A/250 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	69 mm
Product weight	210 g
Colour	White (RAL 9003)
Response time	<= 25 ns
Residual current	0.003 mA
Connections - terminals	Tunnel type terminal, top or bottom 25 mm ² cable(s) rigid Tunnel type terminal, top or bottom 16 mm ² cable(s) flexible Tunnel type terminal, top or bottom 16 mm ² cable(s) flexible with ferrule
Wire stripping length	11 mm
Tightening torque	3.5 N.m

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Okolina

standards	IEC 61643-11: 2011
product certifications	CE EAC
IP degree of protection	On front face: IP40 conforming to IEC 60529 On terminal: IP20 conforming to IEC 60529
IK degree of protection	IK03 conforming to IEC 62262
relative humidity	5...95 %
operating altitude	2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0627 - Schneider Electric declaration of conformity	Compliant - since 0627 - Schneider Electric declaration of conformity
Reference contains SVHC above the threshold - go to CaP for more details	Reference contains SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------