

A9L16293

iQuick PRD40r modularni odvodnik prenapona–3
pola–350 V–s daljinskim prijenosom



Glavno

Range	Acti 9
Product name	Acti 9 iQuick PRD
Product or component type	Surge arrester with pluggable cartridge
Device short name	iQuick PRD
Device application	Distribution
Poles description	3P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	IT 230 TN-C

Komplementarno

Surge arrester class type	Type 2
Surge arrester technology	MOV
[Ue] rated operational voltage	230 V (+/- 10 %) AC 50/60 Hz 400 V (+/- 10 %) AC 50/60 Hz
Nominal discharge current	Common mode: 20 kA L/PE Differential mode: 20 kA L/N
Maximum discharge current	Common mode: 40 kA L/PE
[Uc] maximum continuous operating voltage	Common mode: 350 V L/PE
[Up] voltage protection level	2 kV type 2 common mode L/PE
Disconnecter device type	Integrated circuit breaker - Icu 20 kA
Short-circuit withstand	25 kA
Local signalling	Flag color: white/red
Signalling circuit voltage	2 A/250 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	12.7
Height	94 mm
Width	113.6 mm
Depth	75.9 mm
Product weight	0.69 kg
Colour	White (RAL 9003)
Response time	<= 25 ns
Connections - terminals	Tunnel type terminal, downside 2.5...25 mm ² Tunnel type terminal, upside 2.5...35 mm ²
Tightening torque	2.5 N.m

Okolina

standards	EN 61643-11: 2012 IEC 61643-11: 2011
product certifications	CE
quality labels	NF KEMA-KEUR
IP degree of protection	On front face: IP40 conforming to IEC 60529

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanosti, poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu sadržanih informacija.

	Built-in: IP20 conforming to IEC 60529
IK degree of protection	IK05 conforming to IEC 62262
relative humidity	5...90 %
operating altitude	2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...70 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1742 - Schneider Electric declaration of conformity	Compliant - since 1742 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------