



Glavno

Product or component type	Cartridge
Device short name	C neutral-350
Surge arrester type	Electrical distribution network

Komplementarno

Surge arrester class type	Type 2
Surge arrester technology	GDT
Earthing system	TN TT
[Ue] rated operational voltage	230 V AC 50 Hz
Nominal discharge current	20 kA
Maximum discharge current	65 kA
[Uc] maximum continuous operating voltage	264 V
[Up] voltage protection level	1.5 kV type 2
Local signalling	Flag color: white/red
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	1.3
Height	50 mm
Width	12 mm
Depth	57 mm
Colour	White (RAL 9003)
Material	PBT (polybutylene terephthalate)
Response time	< 25 ns

Okolina

standards	EN 61643-11 IEC 61643-1
product certifications	KEMA-KEUR NF
IP degree of protection	Front face: IP20
relative humidity	5...90 %
operating altitude	0...2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...70 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1742 - Schneider Electric declaration	Compliant - since 1742 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

of conformity

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------