

## A9MEM2010

modularni jednofazni mjerač energije iEM2010 – 230 V – 40 A s impulsom



### Glavno

Range	Acti 9
Product name	Acti 9 iEM2000
Device short name	IEM2010
Product or component type	Energy meter

### Komplementarno

Poles description	1P + N
Type of measurement	Active power
Device application	Sub billing
Accuracy class	Active energy: class 1 according to IEC 62053-21
Analogue input type	Direct input
[In] rated current	40 A
Rated voltage	230 V +/- 20 %
Network frequency	50 Hz 60 Hz
Frequency measurement range	48...62 Hz
Technology type	Electronic
Display type	Electromechanical
Sampling rate	32 samples/cycle
Measurement current	0...40 A
Display digits	7
Maximum value measured	999999.9 kWh
Communication port protocol	-
Communication port support	-
Local signalling	Indicator light (green): power ON Indicator light (yellow) : metering and activity 3200 p/kWh
Number of inputs	0
Number of outputs	1 pulse
Output voltage	5...35 V DC (20 mA)
Impulse duration	120 ms
Power consumption in VA	<= 10 VA
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Power circuit : bottom tunnel type terminalsfor 1 10 mm <sup>2</sup> Remote transfer : top tunnel type terminalsfor 1 4 mm <sup>2</sup>
Tightening torque	Power circuit: 1.2 N.m Remote transfer : 0.8 N.m
Standards	IEC 61557-12 IEC 62053-21
Product certifications	CE MID

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanosti poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Okolina

IP degree of protection	IP40 conforming to IEC 60529
ambient air temperature for operation	-20...70 °C at < 32 A -20...55 °C at >= 32 A
ambient air temperature for storage	-40...70 °C
relative humidity	95 % at 55 °C
colour	White
9 mm pitches	2
width	18 mm
height	95 mm
depth	67 mm
product weight	0.073 kg

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0926 - Schneider Electric declaration of conformity	Compliant - since 0926 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available