



Glavno

Range	Acti 9
Product name	Acti 9 iEM2100
Device short name	IEM2110
Product or component type	Energy meter

Komplementarno

Poles description	1P + N
Type of measurement	Voltage Current Active and reactive power Active and reactive energy
Metering type	Active, reactive, apparent energy (signed, four quadrant)
Device application	Sub billing Multi-tariff Partial meter
Accuracy class	Active energy: class 1 according to IEC 62053-21 Active energy: class B according to EN 50470-3 Reactive energy: class 2 according to IEC 62053-23
Analogue input type	Direct input
[In] rated current	63 A
Rated voltage	230 V +/- 20 %
Network frequency	50 Hz 60 Hz
Frequency measurement range	45...65 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	0...63 A
Display digits	8
Maximum value measured	999999.99 kWh
Information displayed	2 tariff
Communication port protocol	-
Communication port support	-
Local signalling	LED (red) : accuracy checking 1...1000 p/kWh
Number of inputs	1 digital (tariff switching)
Number of outputs	2 pulse
Output voltage	3...33 V AC (90 mA) 5...70 V DC (90 mA)
Impulse duration	30...100 ms
[Us] rated supply voltage	96...276 V AC 50 Hz
Power consumption in VA	<= 2 VA
Power consumption in W	<= 1 W
[Uimp] rated impulse withstand voltage	6 kV 1.2/50 μs
Mounting mode	Clip-on
Mounting support	DIN rail

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
 Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Connections - terminals	Power circuit: bottom tunnel type terminals for 1 1.65...33 mm ² solid cable(s) Power circuit: bottom tunnel type terminals for 1 1.65...33 mm ² stranded cable(s) with cable end Pulse output: top screw clamp terminals for 1 1...4 mm ² solid cable(s) Pulse output: top screw clamp terminals for 1 1...2.5 mm ² stranded cable(s) with cable end
Tightening torque	Power circuit: 2 N.m with PZ2 Pulse output: 0.5 N.m (3.5 mm blade)
Wire stripping length	Power circuit: 17 mm Pulse output: 6 mm
Standards	IEC 62053-21 IEC 62053-23 IEC 62052-11 IEC 62053-31 IEC 62052-31
Product certifications	CE MID conforming to EN 50470-1 MID conforming to EN 50470-3

Okolina

IP degree of protection	IP20 conforming to IEC 60529
overvoltage category	III
pollution degree	2
flame retardance	V0 conforming to UL 94
ambient air temperature for operation	-25...55 °C
ambient air temperature for storage	-25...70 °C
relative humidity	95 %
colour	White
9 mm pitches	4
width	36 mm
height	90 mm
depth	64 mm
product weight	0.175 kg

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1610 - Schneider Electric declaration of conformity	Compliant - since 1610 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold