



Glavno

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L + N
Total number of 18 mm modules	56

Komplementarno

Number of ways	22 ways Aux + N + 1 L + Vigi
Poles configuration for 1 way	1 x 1P + N
Connection pitch	9 mm between phase and neutral
Connector type	Tooth
Distance between way	45 mm
Marking	N L
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	63 A (40 °C)
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	112
Width	1000 mm
Colour	Light grey (RAL 7035)
Range compatibility	Acti 9 iDPN Vigi Multi 9 N40 Vigi Acti 9 iDPN Acti 9 C40 Acti 9 ID C40 Acti 9 DT40 Acti 9 IDc Acti 9 ITG40 Acti 9 C40 Vigi Acti 9 DT40 Vigi

Okolina

standards	IEC 61439-2 IEC 60947-7-1
fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1250 - Schneider Electric declaration of conformity	Compliant - since 1250 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.