



Glavno

Range	Acti 9 Clario Librio Prodis
Product or component type	OC and fault contact with PLC interface
Device short name	OF+SD 24
Signal contacts composition	1 NO + 1 NC
[In] rated current	2...100 mA at 24 V DC +/- 20 %
9 mm pitches	1

Komplementarno

Range compatibility	Acti 9 C120 Acti 9 C60H-DC Acti 9 DPN Acti 9 iDPN Acti 9 DPN Vigi Acti 9 RCCB-ID Connectors Ti24 Acti 9 C60PV-DC Acti 9 C40 Acti 9 ID C40 Acti 9 DT40 Acti 9 DT60 Acti 9 IDc Acti 9 C120NA-DC Acti 9 ITG40 Acti 9 SW60-DC Acti 9 C60NA-DC
[U _i] rated insulation voltage	500 V conforming to IEC 60664-1
[U _{imp}] rated impulse withstand voltage	6 kV conforming to IEC 60664-1
Local signalling	Mechanical indicator
Mounting mode	Fixed
Mounting support	DIN rail
Height	85.5 mm
Width	9 mm
Depth	73.5 mm
Product weight	28 g
Colour	White
Electrical durability	20000 cycles conforming to IEC 60947-5-4
Connections - terminals	Spring-loaded terminal Ti24 in top 1 cable(s) 0.5...1.5 mm ² rigid Spring-loaded terminal Ti24 in top 1 cable(s) 0.5...1.5 mm ² flexible
Wire stripping length	10 mm

Okolina

standards	IEC 60947-5-1 IEC 60947-5-4
quality labels	CE
pollution degree	2 conforming to IEC 60664-1
overvoltage category	III
tropicalisation	2 conforming to IEC 60947-5-1
relative humidity	93 % at 40 °C

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poipunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1203 - Schneider Electric declaration of conformity	Compliant - since 1203 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available