



Glavno

Range	Acti 9 Clario Librio Prodis
Product or component type	Fault contact
Device short name	SD
Signal contacts composition	1 C/O
[In] rated current	3 A at 380...415 V AC - 50/60 Hz 6 A at 220...240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC
9 mm pitches	1

Komplementarno

Range compatibility	Acti 9 iDPN Vig Acti 9 C120 Acti 9 C60H-DC Acti 9 iDPN Acti 9 DPN Vig Acti 9 C60PV-DC Acti 9 C40 Acti 9 ID C40 Acti 9 DT40 Acti 9 DT60 Acti 9 IDc Acti 9 C120NA-DC Acti 9 ITG40 Acti 9 SW60-DC Acti 9 C60NA-DC Acti 9 C40 Vig Acti 9 DT40 Vig
Mounting mode	Fixed
Mounting support	DIN rail
Height	85.3 mm
Width	9 mm
Depth	73.5 mm
Product weight	30 g
Colour	White
Connections - terminals	Clamp terminal in bottom 2 cable(s) 1.5 mm ² flexible Clamp terminal in bottom 1 cable(s) 0.5...2.5 mm ² rigid Clamp terminal in bottom 2 cable(s) 1.5 mm ² flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

Okolina

standards	EN/IEC 60947-5-1
product certifications	ASEFA ASTA KEMA LCIE
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
pollution degree	3 conforming to EN/IEC 60947-5-1

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

tropicalisation	2 conforming to EN/IEC 60947-5-1
ambient air temperature for operation	-25...50 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1001 - Schneider Electric declaration of conformity	Compliant - since 1001 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------