

A9N26946

MX Paralelni okidač MX plus 1 OF 220 – 415 V AC
DC



Glavno

Range	Acti 9 Clario Librio Prodis
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Ie] rated operational current	3 A at 415 V AC 6 A at <= 240 V AC
[Uc] control circuit voltage	110...130 V DC 100...415 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	C40 C60 DT40 IDPN DT60 C120 DPN Vigi ITG40 IDc ID C40

Komplementarno

Range compatibility	Acti 9: Acti 9 iDPN Acti 9: Acti 9 DT40 Acti 9: Acti 9 C40 Acti 9: Acti 9 IDc Acti 9: Acti 9 ID C40 Acti 9: Acti 9 ITG40 Acti 9: Acti 9 C120 Acti 9: Acti 9 C60H-DC Acti 9: Acti 9 C60NA-DC Acti 9: Acti 9 C60PV-DC Acti 9: Acti 9 DPN Vigi Acti 9: Acti 9 DT60 Acti 9: Acti 9 ID Acti 9: Acti 9 DPN
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	73.5 mm
Product weight	65 g
Colour	White
Connections - terminals	Screw clamp terminal bottom 2 cable(s) 1.5 mm ² flexible Screw clamp terminal bottom 2 cable(s) 1.5 mm ² flexible with ferrule Screw clamp terminal bottom 1 cable(s) 0.5...2.5 mm ² rigid
Wire stripping length	9 mm bottom
Tightening torque	1 N.m bottom

Okolina

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

standards	EN/IEC 60947-5-1
product certifications	ASEFA ASTA KEMA LCIE
tropicalisation	2 conforming to EN/IEC 60947-5-1
relative humidity	95 % at 55 °C
ambient air temperature for operation	-25...50 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1216 - Schneider Electric declaration of conformity	Compliant - since 1216 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------