



Glavno

| | |
|------------------------------|--|
| Range | Acti 9 Clario Librio Prodis |
| Product or component type | Undervoltage release |
| Device short name | MN |
| [Uc] control circuit voltage | 220...240 V AC 50/60 Hz |
| Control type | Standard |
| 9 mm pitches | 2 |
| Product compatibility | C40 C60 DT40 IDPN DT60 C120 DPN Vigi ITG40 IDc ID C40 |

Komplementarno

| | |
|-------------------------|---|
| Range compatibility | Acti 9: Acti 9 iDPN Acti 9: Acti 9 DT40 Acti 9: Acti 9 C40 Acti 9: Acti 9 IDc Acti 9: Acti 9 ID C40 Acti 9: Acti 9 ITG40 Acti 9: Acti 9 C120 Acti 9: Acti 9 C60H-DC Acti 9: Acti 9 C60NA-DC Acti 9: Acti 9 C60PV-DC Acti 9: Acti 9 DPN Vigi Acti 9: Acti 9 DT60 Acti 9: Acti 9 ID Acti 9: Acti 9 DPN |
| Local signalling | Action indicator |
| Mounting mode | Fixed |
| Mounting support | 35 mm symmetrical DIN rail |
| Height | 82.5 mm |
| Width | 18 mm |
| Depth | 73.5 mm |
| Product weight | 66 g |
| Colour | White |
| Connections - terminals | Clamp terminal 1 cable(s) 2.5 mm ² flexible Clamp terminal 1 cable(s) 2.5 mm ² rigid Clamp terminal 2 cable(s) 1.5 mm ² flexible Clamp terminal 2 cable(s) 1.5 mm ² rigid |
| Wire stripping length | 9 mm |
| Tightening torque | 1 N.m |

Okolina

| | |
|------------------------|------------------|
| standards | EN/IEC 60947-5-1 |
| product certifications | ASEFA ASTA |

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

KEMA
LCIE

| | |
|---------------------------------------|----------------------------------|
| tropicalisation | 2 conforming to EN/IEC 60947-5-1 |
| relative humidity | 95 % at 55 °C |
| ambient air temperature for operation | -25...50 °C |
| ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1216 - Schneider Electric declaration of conformity | Compliant - since 1216 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Available | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|