

## A9R17463

iID – zaštita od propuštanja uzemljenja – 4P – 63 A – 500 mA – Tip AC



### Glavno

|                                     |   |
|-------------------------------------|---|
| Range                               | Acti 9                                  |
| Product name                        | Acti 9 iID                              |
| Product or component type           | Residual current circuit breaker (RCCB) |
| Device short name                   | iID                                     |
| Poles description                   | 4P                                      |
| Neutral position                    | Left                                    |
| [In] rated current                  | 63 A                                    |
| Network type                        | AC                                      |
| Earth-leakage sensitivity           | 500 mA                                  |
| Earth-leakage protection time delay | Selective                               |
| Earth-leakage protection class      | Type AC                                 |

### Komplementarno

|   |  |
|---|--|
| Device location in system               | Outgoer  |
| Network frequency                       | 50/60 Hz   |
| [Ue] rated operational voltage          | 380...415 V AC 50/60 Hz  |
| Residual current tripping technology    | Voltage independent  |
| Rated breaking and making capacity      | Im 1500 A<br>Idm 1500 A  |
| Rated conditional short-circuit current | 10 kA  |
| [Ui] rated insulation voltage           | 500 V AC 50/60 Hz  |
| [Uimp] rated impulse withstand voltage  | 6 kV   |
| Contact position indicator              | Yes  |
| Control type                            | Toggle   |
| Mounting mode                           | Clip-on  |
| Mounting support                        | DIN rail   |
| 9 mm pitches                            | 8  |
| Height                                  | 91 mm  |
| Width                                   | 72 mm  |
| Depth                                   | 73.5 mm  |
| Product weight                          | 0.37 kg  |
| Colour                                  | White  |
| Mechanical durability                   | 20000 cycles   |
| Electrical durability                   | 15000 cycles AC-1  |
| Locking options description             | Padlocking device  |
| Connections - terminals                 | Single terminal, top or bottom rigid wire(s) 1...35 mm <sup>2</sup> max<br>Single terminal, top or bottom flexible wire(s) 1...25 mm <sup>2</sup> max<br>Single terminal, top or bottom flexible with ferrule wire(s) 1...25 mm <sup>2</sup> max |
| Wire stripping length                   | 14 mm (top or bottom)  |
| Tightening torque                       | 3.5 N.m (top or bottom)  |

### Okolina

|                         |                              |
|-------------------------|------------------------------|
| standards               | EN/IEC 61008-1               |
| IP degree of protection | IP20 conforming to IEC 60529 |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

|                                       |   |
|---------------------------------------|---|
|                                       | IP40for modular enclosure conforming to IEC 60529                   |
| pollution degree                      | 3   |
| electromagnetic compatibility         | 8/20 $\mu$ s impulse withstand, 3000 A conforming to EN/IEC 61008-1 |
| ambient air temperature for operation | -5...60 °C  |
| ambient air temperature for storage   | -40...85 °C   |

### Offer Sustainability

|   |   |
|---|---|
| Green Premium product   | Green Premium product   |
| Compliant - since 0627 - Schneider Electric declaration of conformity | Compliant - since 0627 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold                     | Reference not containing SVHC above the threshold                     |
| Available   | Available   |
| Need no specific recycling operations                                 | Need no specific recycling operations                                 |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|