

A9R75240

Acti 9 iID K - sklopka rezidualne struje- 2P - 40A - 300mA - tip AC



Glavno

| | |
|-------------------------------------|-----------------------------------------|
| Range | Acti 9 |
| Product name | Acti 9 iID K |
| Product or component type | Residual current circuit breaker (RCCB) |
| Device short name | iID K |
| Poles description | 2P |
| Neutral position | Left |
| [In] rated current | 40 A |
| Network type | AC |
| Earth-leakage sensitivity | 300 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC |
| Quality labels | VDE |

Komplementarno

| | |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device location in system | Outgoer |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 220...240 V AC 50/60 Hz |
| Residual current tripping technology | Voltage independent |
| Rated breaking and making capacity | Im 500 A Idm 500 A |
| Rated conditional short-circuit current | With gL63: Inc 4.5 kA With K60: Inc 6 kA With C60: Inc 6 kA |
| [Ui] rated insulation voltage | 440 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Contact position indicator | No |
| Control type | Toggle |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 4 |
| Height | 85 mm |
| Width | 36 mm |
| Depth | 69 mm |
| Product weight | 0.21 kg |
| Colour | White |
| Mechanical durability | 5000 cycles |
| Electrical durability | 2000 cycles AC-1 |
| Locking options description | Padlocking device |
| Connections - terminals | Tunnel type terminals, top or bottom flexible wire(s) 1...25 mm ² max Tunnel type terminals, top or bottom flexible with ferrule wire(s) 1...25 mm ² max Tunnel type terminals, top or bottom rigid wire(s) 1...35 mm ² max |
| Wire stripping length | 16 mm (top or bottom) |
| Tightening torque | 3.5 N.m (top or bottom) |

Okolina

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|---------------------------------------|-----------------------------------------------------------------------------------|
| standards | EN/IEC 61008-1 |
| IP degree of protection | IP20 conforming to IEC 60529 IP40for modular enclosure conforming to IEC 60529 |
| pollution degree | 2 |
| electromagnetic compatibility | 8/20 μ s impulse withstand, 200 A conforming to EN/IEC 61008-1 |
| ambient air temperature for operation | -5...60 °C |
| ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|-----------------------------------------------------------------------|-----------------------------------------------------------------------|
| Green Premium product | Green Premium product |
| Compliant - since 1001 - Schneider Electric declaration of conformity | Compliant - since 1001 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |