



Glavno

| | |
|---------------------------|---------------------|
| Range | Acti 9 |
| Product name | Acti 9 iSW |
| Product or component type | Switch disconnecter |
| Device short name | ISW |
| Device application | Control |
| Poles description | 2P |
| Utilisation category | AC-22A |

Komplementarno

| | |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| [Ie] rated operational current | 20 A 250 V AC 50/60 Hz |
| [Ue] rated operational voltage | 415 V AC 50/60 Hz |
| [Ui] rated insulation voltage | 250 V AC 50/60 Hz conforming to IEC EN 60669-1 |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Control type | Toggle |
| Local signalling | ON/OFF indication and lamp |
| Signalling circuit voltage | AC: 230 V 50/60 Hz |
| Mounting mode | Fixed |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Height | 77 mm |
| Width | 18 mm |
| Depth | 70 mm |
| Colour | White |
| Mechanical durability | 300000 cycles |
| Electrical durability | 30000 cycles |
| Connections - terminals | Tunnel type terminals: rigid Tunnel type terminals: flexible Tunnel type terminals: flexible with ferrule |
| Wire stripping length | 9 mm |
| Tightening torque | 1.2 N.m |

Okolina

| | |
|---------------------------------------|----------------|
| standards | IEC EN 60669-1 |
| IP degree of protection | IP4 |
| pollution degree | 2 |
| tropicalisation | 2 |
| relative humidity | 95 % at 55 °C |
| ambient air temperature for operation | -20...50 °C |
| ambient air temperature for storage | -40...70 °C |

Offer Sustainability

| | |
|---------------------------------------------------------|-----------------------------------------------------------------------|
| Green Premium product | Green Premium product |
| Compliant - since 1741 - Schneider Electric declaration | Compliant - since 1741 - Schneider Electric declaration of conformity |

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

of conformity

| | |
|---------------------------------------------------|---------------------------------------------------|
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Available | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|