



### Glavno

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L
Total number of 18 mm modules	12

### Komplementarno

Number of ways	4 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	54 mm
Marking	L1 L2 L3
Insulation	Insulated
Device presentation	Cutable
[Ie] rated operational current	100 A ( 40 °C )
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	24
Width	220 mm
Colour	White ( RAL 9003 )
Range compatibility	Multi 9 C60 Acti 9 iK60 Acti 9 iC60 Acti 9 iLD Acti 9 iLD K Acti 9 iSW Acti 9 iSW-NA

### Okolina

standards	IEC 61439-2 IEC 60947-7-1
fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1336 - Schneider Electric declaration of conformity	Compliant - since 1336 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

**Contractual warranty**

Warranty period	18 months
-----------------	-----------