

ACW7M129012

lačna sklopka ACW 69 bara – 2 podesiva praga – 1CO



Glavno

Range of product	OsiSense XM
Pressure sensor name	ACW
Pressure sensor type	Electromechanical pressure sensor
Product specific application	For regulation between 2 thresholds
Scale type	Adjustable differential
Contacts type and composition	1 C/O, snap action
Cable entry	1 entry tapped for Pg 13.5 cable gland, cable outer diameter: 9...13 mm conforming to NF C 68-300
Fluid connection type	G 1/4 (female) conforming to ISO 228
Materials in contact with fluid	Phosphor bronze
Pressure sensor size	69 bar
Adjustable range of switching point on falling pressure	10...69 bar
Adjustable range of switching point on rising pressure	15.9...79 bar
Pressure actuator	Bellows
Electrical circuit type	Control circuit

Komplementarno

Electrical connection	Screw-clamp terminals, 1 x 1...2 x 2.5 mm ²
Controlled fluid	Air (-73...125 °C) Hydraulic oil (-73...125 °C) Non-corrosive fluid (-73...125 °C)
Short-circuit protection	10 A by gG cartridge fuse
Enclosure material	Zinc alloy
Possible differential minimum at low setting	5.9 bar
Possible differential minimum at high setting	5.9 bar
Possible differential maximum at low setting	0.4 bar
Possible differential maximum at high setting	10 bar
Maximum permissible pressure - per cycle	140 bar
Mechanical durability	1000000 cycles
Setting	External
Local display	Without
Terminals description ISO n°1	(1-2)NC (3-4)NO
Width	88 mm
Height	221 mm
Depth	68 mm
Product weight	2.1 kg

Okolina

protective treatment	TC
standards	CE EN/IEC 60947-5-1
product certifications	CSA UL recognized EAC
IP degree of protection	IP65 conforming to EN/IEC 60529

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

ambient air temperature for operation

-56...85 °C

Offer Sustainability

Not Green Premium product

Not Green Premium product

Will not be Compliant

Will not be Compliant

Contractual warranty

Warranty period

18 months
