



Main

Range	Altira
Product or component type	Data socket
Device presentation	Mechanism with central plate
Cable shielding type	STP
Data socket type	RJ45 - 8 5e
Cover plate colour tint	Polar white RAL 9003)
Wiring device additional information	Label-holder with label Retractable shutter

Complementary

Range compatibility	OptiLine 45 OptiLine 70 with Altira adaptor
Communication port protocol	PoE+ (Power over Ethernet)
Number of modules	2 modules
Product destination	Altira fixing frame Floor box Duct
Product compatibility	Actassi s-one
Socket number	2
Organization of wire	Shielded twisted pair
Connections - terminals	Self-stripping terminals
Marking	Colour coding
Installation direction	Straight
Device mounting	Flush
Fixing mode	Clip-in By clips shield
Surface treatment	Untreated
Maksimalna visina	45 mm
Maksimalna širina	45 mm
Maksimalna dubina	45 mm

Environment

IP degree of protection	IP20
IK degree of protection	IK02
Environmental characteristic	Oil Bleach Window-cleaning fluid Alcohol Hydrogen peroxide (H2O2) Petrol UV resistant Acetone Liquid soap Ammonia
Environmental health and issues	Halogen free
Standards	RoHS compliant ISO/IEC 11801 Ed.2.2:2011 IEC 60603-7-1:2010

Offer Sustainability

Status održive ponude	Proizvod Green Premium
REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------