


ALB45032

Altira – ključno tipkalo u slučaju nužde – 1–smjerno – 10 A



Glavno

Range of product	Altira
Range	Altira
Product or component type	Emergency key push-button
Device presentation	Mechanism
Switch application	Emergency

Komplementarno

Wiring device mounting	Flush Surface
Device mounting	Flush Surface
Product destination	OptiLine 45 installation system
Switch function	1-way
Rated current	6 A - 250 V AC 50 Hz
Actuator	Push-button
Number of modules	2 modules
Fixing mode	Clip-in
Connections - terminals	Screwless terminals 3
Clamping connection capacity	2 x 1.5...2 x 2.5 mm ² for solid cable(s) 2 x 1.5...2 x 2.5 mm ² for stranded cable(s)
Material	PBT (polybutylene terephthalate)
Surface finish	Satin
Embedding depth	21.7 mm
Height	45 mm
Width	45 mm
Depth	33.8 mm
Product weight	0.083 kg

Okolina

standards	EN 60529 EN 62262
ambient air temperature for operation	5...50 °C
ambient air temperature for storage	-15...60 °C
IK degree of protection	IK08
IP degree of protection	IP44
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

	Hydrogen peroxide (H2O2)
environmental health and issues	Halogen free

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0734 - Schneider Electric declaration of conformity	Compliant - since 0734 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------