



Glavno

Range	Altira
Range of product	Altira
Product or component type	Switch
Device presentation	Mechanism
Switch additional information	Without lamp
Cover plate colour tint	White (RAL 9010)

Komplementarno

Wiring device mounting	Flush Surface
Device mounting	Flush Surface
Product destination	OptiLine 45 installation system Fixing frame Lens
Switch function	2-way switch
Rated current	16 A - 250 V AC
Actuator	Rocker
Number of modules	2 modules
Fixing mode	Clip-in
Pilot light	Indicator
Connections - terminals	6 x screwless terminals
Clamping connection capacity	2 x 1.5...2 x 2.5 mm ² for rigid cable(s) 2 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	PC for mechanism cover
Surface treatment	Untreated
Surface finish	Satin
Embedding depth	21 mm
Height	45 mm
Width	45 mm
Depth	28 mm
Product weight	0.034 kg

Okolina

standards	EN 60529 EN 62262 IEC EN 60669-1
ambient air temperature for operation	-5...50 °C
ambient air temperature for storage	-15...60 °C
IK degree of protection	IK04
IP degree of protection	IP21 D
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap

Oil
Petrol
UV resistant
Window-cleaning fluid
Hydrogen peroxide (H2O2)

environmental health and issues

Halogen free

Offer Sustainability

Green Premium product

Green Premium product

Compliant - since 1834 - Schneider Electric declaration of conformity

Compliant - since 1834 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Available

Available

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
