



## Glavno

Range of product	Altira
Range	Altira
Product or component type	Buzzer
Device presentation	Mechanism
Cover plate colour tint	White (RAL 9010)

## Komplementarno

Wiring device mounting	Flush Surface
Device mounting	Flush Surface
Product destination	OptiLine 45 installation system
[Ue] rated operational voltage	230 V AC 24 V DC 8 V AC
Number of modules	2 modules
Fixing mode	Clip-in
Connections - terminals	Screw terminals
Clamping connection capacity	2 x 1.5 mm <sup>2</sup> for flexible cable(s) 2 x 1.5 mm <sup>2</sup> for solid stranded cable(s)
Acoustic level	70 dB
Material	ABS + PC
Surface finish	Matt
Embedding depth	30.8 mm
Height	45 mm
Width	45 mm
Depth	34 mm
Product weight	0.034 kg

## Okolina

product certifications	CE GOST
ambient air temperature for operation	5...50 °C
ambient air temperature for storage	-15...60 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid Hydrogen peroxide (H2O2)
environmental health and issues	Halogen free

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružica ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------