

ALB45545

Altira – ravna žaruljica indikatora s difuzorom 45 mm
– bez žaruljice – crvena



Glavno

Range of product	Altira
Range	Altira
Product or component type	Flat indicator lamp with 45 mm diffuser
Device presentation	Mechanism
Wiring device additional information	Without lamp
Light block colour	Red

Komplementarno

Wiring device mounting	Flush Surface
Device mounting	Flush Surface
Product destination	OptiLine 45 installation system
[Ue] rated operational voltage	250 V AC
Number of modules	2 modules
Fixing mode	Clip-in
Cable cross section	1.5...2.5 mm ² for flexible cable 1.5...2.5 mm ² for rigid cable 1.5...2.5 mm ² for solid stranded cable
Material	PC
Height	45 mm
Width	45 mm
Depth	27 mm
Product weight	0.02 kg

Okolina

ambient air temperature for operation	5...50 °C
ambient air temperature for storage	-15...60 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid Hydrogen peroxide (H2O2)
environmental health and issues	Halogen free

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Available

Available

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
