

Podatkovni list proizvoda

Karakteristike

ALB46287

Altira – 1 SO – 2P+E s roletama – bočno uzemljenje – Alu.



Glavno

Range	Altira
Product or component type	Socket-outlet
Range compatibility	OptiLine 45 fixing frame OptiLine 70 with Altira adaptor fixing frame
Device presentation	Mechanism
Number of power socket outlets	1 2P + E German
Outlet standard description	Side earth
Socket additional information	Shuttered
Colour tint	Aluminium

Komplementarno

Product destination	Fixing frames
Range compatibility	OptiLine 45 OptiLine 70 with Altira adaptor
Rated current	16 A - 250 V - AC - 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Connections - terminals	Screwless terminals
Clamping connection capacity	4 x 1.5...4 x 2.5 mm ² for rigid cable(s) 4 x 1.5...4 x 2.5 mm ² for solid stranded cable(s)
Material	PC for mechanism cover
Surface treatment	Untreated
Surface finish	Satin
Standards	EN 60529 EN 62262 IEC 60884-1 NFC 61-314
Height	45 mm
Width	45 mm
Depth	39 mm

Okolina

ambient air temperature for operation	5...50 °C
ambient air temperature for storage	-15...60 °C
IK degree of protection	IK02
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid Hydrogen peroxide (H2O2)
environmental health and issues	Halogen free

Offer Sustainability

Not Green Premium product	Not Green Premium product
---------------------------	---------------------------

Compliant - since 0852 - Schneider Electric declaration of conformity Compliant - since 0852 - Schneider Electric declaration of conformity

Available

Available

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months