

Glavno

Range	TeSys
Product name	TeSys CASK
Product or component type	Control relay
Device short name	CA2SK
Contact application	Control circuit
Utilisation category	AC-15 DC-13
Pole contact composition	1 NO + 1 NC
[Ue] rated operational voltage	<= 690 V <= 400 Hz
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	110 V AC 50/60 Hz

Komplementarno

[Ith] conventional free air thermal current	10 A at <= 55 °C
Associated fuse rating	10 A gL conforming to VDE 0660 10 A gL conforming to IEC 60947
[Ui] rated insulation voltage	690 V conforming to BS 5424 690 V conforming to IEC 60947 690 V conforming to VDE 0110 group C 690 V conforming to UL 508 690 V conforming to CSA C22.2 No 14
Mounting support	Plate Rail
Connections - terminals	Screw clamp terminals 2 cable(s) 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 1 cable(s) 1.5...6 mm ² - cable stiffness: solid Screw clamp terminals 1 cable(s) 0.5...6 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable(s) 0.35...6 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 0.35...1.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 0.35...2.5 mm ² - cable stiffness: flexible - without cable end
Tightening torque	0.8 N.m - on screw clamp terminals pozidriv No 1
Control circuit voltage limits	0.85...1.1 Uc at 50 °C operational 0.2...0.75 Uc at 50 °C drop-out
Operating time	6...8 ms coil de-energisation and NO opening 7...14 ms coil energisation and NO closing 8...16 ms coil energisation and NC opening 8...10 ms coil de-energisation and NC closing
Mechanical durability	10 Mcycles
Operating rate	1200 cyc/h
Inrush power in VA	16 VA at 20 °C
Hold-in power consumption in VA	4.2 VA at 20 °C
Heat dissipation	1.4 W
Height	56 mm
Width	27 mm
Depth	55.5 mm
Product weight	0.132 kg

Okolina

standards	BS 5424 IEC 60947
-----------	----------------------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popunnu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

NF C 63-110
VDE 0660

product certifications	CULus
IP degree of protection	IP2x
protective treatment	TC conforming to IEC 60068
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-50...70 °C
operating altitude	2000 m without derating in temperature

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0718 - Schneider Electric declaration of conformity	Compliant - since 0718 - Schneider Electric declaration of conformity
Reference contains SVHC above the threshold - go to CaP for more details	Reference contains SVHC above the threshold