



Glavno

| | |
|---------------------------|--|
| Range of product | Acti 9 |
| Product name | Acti 9 IC |
| Product or component type | Programmable astronomical twilight switch |
| Device short name | IC Astro |
| Number of channels | 1 |
| Battery type | Lithium |
| Type of setting | Weekly programming |
| Function available | Automatic time changeover Coupling with time switch functions Control by calculation of sunrise/sunset times |
| User language | Bulgarian Croatian English French Greek Hungarian Polish Portuguese Romanian Serbian Slovak Slovene Spanish Czech |
| Product compatibility | Mechanical compatibility with electrical distribution comb busbars |

Komplementarno

| | |
|---------------------------|---|
| Device application | Building |
| Measurement accuracy | +/- 1 s/day |
| Control type | By calculation of sunrise/sunset times |
| Load type | 230 V AC halogen lamp, (2300 W) 230 V AC incandescent lamp, (2300 W) 3 dual mounted fluorescent tube, balast : electronic, (2 x 58 W) 5 dual mounted fluorescent tube, balast : electronic, (2 x 36 W) Non-corrected fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected fluorescent tube, balast : conventional, (10 x 36 W) Serial-corrected fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected fluorescent tube, balast : conventional, (2 x 100 W) Non-corrected fluorescent tube, balast : conventional, (20 x 58 W) Serial-corrected fluorescent tube, balast : conventional, (20 x 58 W) Non-corrected fluorescent tube, balast : conventional, (26 x 36 W) Serial-corrected fluorescent tube, balast : conventional, (26 x 36 W) Fluorescent tube, balast : electronic, (6 x 58 W) Parallel-corrected fluorescent tube, balast : conventional, (6 x 58 W) Fluocompact lamp, balast : electronic, (7 x 11 W) Fluocompact lamp, balast : electronic, (7 x 15 W) Fluocompact lamp, balast : electronic, (7 x 20 W) Fluocompact lamp, balast : electronic, (9 x 7 W) Fluorescent tube, balast : electronic, (9 x 36 W) Dual mounted fluorescent tube, balast : conventional, (26 x 36 W) Dual mounted fluorescent tube, balast : conventional, (20 x 58 W) Dual mounted fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected mercury and sodium vapour lamps, (250 VA) |
| Power consumption in VA | 3 VA |
| Maximum switching current | 10 A - 250 V AC pf = 0.6 |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|--------------------------------|---|
| | 16 A - 250 V AC pf = 1 |
| [Ue] rated operational voltage | 230 V (+10 % -15 %) AC 50/60 Hz |
| Display type | Backlit LCD |
| Maximum number of switchings | 84 |
| Minimum interval duration | 1 min |
| Backup time | 6 years time and program saving |
| Mounting support | DIN rail |
| 9 mm pitches | 5 |
| Connections - terminals | X 2 screwless terminals: <= 2.5 mm ² |
| Height | 85 mm |
| Width | 45 mm |
| Depth | 65 mm |
| Product weight | 132 g |

Okolina

| | |
|---------------------------------------|-------------|
| ambient air temperature for operation | -25...45 °C |
| IP degree of protection | IP20 B |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1019 - Schneider Electric declaration of conformity | Compliant - since 1019 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|