

CCT15243

Acti 9 – IC Astro – 2C programibilna svjetlosna sklopka



Glavno

Range of product	Acti 9
Product name	Acti 9 IC
Product or component type	Programmable astronomical twilight switch
Device short name	IC Astro
Number of channels	2
Battery type	Lithium
Provided equipment	Memory key
Type of setting	Weekly programming
Function available	Automatic time changeover Coupling with time switch functions Control by calculation of sunrise/sunset times
User language	Bulgarian Croatian English French Greek Hungarian Polish Portuguese Romanian Serbian Slovak Slovene Spanish Czech
Product compatibility	Mechanical compatibility with electrical distribution comb busbars

Komplementarno

Device application	Building
Measurement accuracy	+/- 1 s/day
Control type	By calculation of sunrise/sunset times
Load type	230 V AC halogen lamp, (2300 W) 230 V AC incandescent lamp, (2300 W) 3 dual mounted fluorescent tube, balast : electronic, (2 x 58 W) 5 dual mounted fluorescent tube, balast : electronic, (2 x 36 W) Non-corrected fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected fluorescent tube, balast : conventional, (10 x 36 W) Serial-corrected fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected fluorescent tube, balast : conventional, (2 x 100 W) Non-corrected fluorescent tube, balast : conventional, (20 x 58 W) Serial-corrected fluorescent tube, balast : conventional, (20 x 58 W) Non-corrected fluorescent tube, balast : conventional, (26 x 36 W) Serial-corrected fluorescent tube, balast : conventional, (26 x 36 W) Fluorescent tube, balast : electronic, (6 x 58 W) Parallel-corrected fluorescent tube, balast : conventional, (6 x 58 W) Fluocompact lamp, balast : electronic, (7 x 11 W) Fluocompact lamp, balast : electronic, (7 x 15 W) Fluocompact lamp, balast : electronic, (7 x 20 W) Fluocompact lamp, balast : electronic, (9 x 7 W) Fluorescent tube, balast : electronic, (9 x 36 W) Dual mounted fluorescent tube, balast : conventional, (26 x 36 W) Dual mounted fluorescent tube, balast : conventional, (20 x 58 W) Dual mounted fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected mercury and sodium vapour lamps, (250 VA)
Power consumption in VA	6 VA

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poipunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
[Ue] rated operational voltage	230 V (+10 % -15 %) AC 50/60 Hz
Display type	Backlit LCD
Maximum number of switchings	84
Minimum interval duration	1 min
Backup time	6 years time and program saving
Mounting support	DIN rail
9 mm pitches	5
Connections - terminals	X 2 screwless terminals: <= 2.5 mm ²
Height	85 mm
Width	45 mm
Depth	65 mm
Product weight	132 g

Okolina

ambient air temperature for operation	-25...45 °C
IP degree of protection	IP20 B

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1426 - Schneider Electric declaration of conformity	Compliant - since 1426 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------