



#### Main

Range of product	Acti 9
Product or component type	Wall mounted cell
Function available	Horizontally orientable

#### Complementary

Range compatibility	Acti9 Acti 9 IC IC100 twilight switch Acti9 Acti 9 IC IC2000 twilight switch Acti9 Acti 9 IC IC2000P+ programmable twilight switch with time switch function
Cable length	50 m
Light intensity adjustment	2...2000 lux
Mounting location	Outdoor
Maksimalna visina	95 mm
Maksimalna širina	48 mm
Maksimalna dubina	45 mm
Neto težina	40,5 g
Market segment	Residential Small commercial
Compatibility code	Wall mounted cell




#### Environment

Ambient air temperature for operation	-40...70 °C
Ambient air temp for storage/transportation	-40...70 °C
Relative humidity	100 %
IP degree of protection	IP55

#### Broj pakirnih jedinica

Vrsta pakirne jedinice Paketa 1	PCE
Vrsta pakirne jedinice Paketa 2	BB1
Vrsta pakirne jedinice Paketa 3	S03

#### Offer Sustainability

Direktiva EU RoHS	Sukladno  <a href="#">Izjava EU RoHS</a>
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	 <a href="#">Da</a>
Propis RoHS za Kinu	 <a href="#">Izjava RoHS Za Kinu</a>

Izjava o očuvanju okoliša	<a href="#">Ekološki Profil Proizvoda</a>
Profil cirkularnosti	<a href="#">Informacije O Kraju Vijeka Trajanja</a>
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.