

CCT15367

Acti 9 – IH – mehanički vremenski prekidač – 7 dana
– 200 sati memorije



Glavno

Range	Acti 9
Product name	Acti 9 IH
Device short name	IH
Product or component type	Mechanical time switch
Number of channels	1
Function available	Manual time changeover

Komplementarno

Device application	Building
Load type	230 V AC halogen lamp, (1100 W) 230 V AC incandescent lamp, (1100 W) Dual mounted fluorescent tube, balast : conventional, (2 x 100 W) Dual mounted fluorescent tube, balast : conventional, (2 x 58 W) Non-corrected fluorescent tube, balast : conventional, (100 W) Non-corrected fluorescent tube, balast : conventional, (40 W) Non-corrected fluorescent tube, balast : conventional, (58 W) Parallel-corrected fluorescent tube, balast : conventional, (40 W) Parallel-corrected fluorescent tube, balast : conventional, (58 W) Serial-corrected fluorescent tube, balast : conventional, (100 W) Serial-corrected fluorescent tube, balast : conventional, (40 W) Serial-corrected fluorescent tube, balast : conventional, (58 W)
Cycle duration	7 days
Measurement accuracy	+/- 1 s/day
Maximum number of switchings	42 on - 42 off
Minimum interval duration	2 h
Type of setting	Manual time changeover
Measurement accuracy	+/- 1 s/day 20 °C
Power consumption in VA	2.5 VA
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
Battery life	6 yr
Backup time	200 h time and program saving 230 V AC 100 h time and program saving 110 V AC
Mounting support	DIN rail
9 mm pitches	6
Colour tint	White (RAL 9003)
Connections - terminals	Screwless terminals
IP degree of protection	IP20 B
Width	54 mm
Height	90 mm
Depth	66 mm
Product weight	0.2 kg

Okolina

ambient air temperature for operation	-20...55 °C
---------------------------------------	-------------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Offer Sustainability

Green Premium product

Green Premium product

Compliant - since 1426 - Schneider Electric declaration of conformity

Compliant - since 1426 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Available

Available

Contractual warranty

Warranty period

18 months