



Glavno

Range	Acti 9
Product name	Acti 9 IC
Product or component type	Twilight switch
Device short name	IC2000
Provided equipment	Wall-mounted cell
Function available	Cabling test function with a push-button on front face

Komplementarno

Device application	Building
Number of channels	1
Load type	(400 VA) Balast : conventional, (1500 VA) Balast : conventional, (2300 VA) Balast : conventional, (2300 VA) Balast : conventional, (2300 VA) Balast : conventional, (400 VA) (2300 W) (2300 W) Balast : electronic, (300 VA) Balast : electronic, (7 x 15 W) Balast : electronic, (7 x 20 W) Balast : electronic, (7 x 23 W) Balast : electronic, (9 x 7 W) Balast : electronic, (7 x 11 W)
Power consumption in VA	6 VA
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
[Ue] rated operational voltage	230 V (+10 % -15 %) AC 50/60 Hz
Opening distance	< 3 mm
Status LED	Green LED : threshold reached Red LED : brightness less than the threshold
Time delay	>= 60 s (on closing) >= 60 s (on breaking contact)
Mounting support	DIN rail
9 mm pitches	5
Light intensity adjustment	2...2000 lux
Connections - terminals	X 2 screwless terminals: <= 2.5 mm ²
Electrical insulation class	Class II
Height	85 mm
Width	45 mm
Depth	65 mm
Product weight	280 g
Control type	By brightness detection

Okolina

standards	EN 60529 EN 60669
ambient air temperature for operation	-25...50 °C

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

IP degree of protection

IP20 B

Offer Sustainability

Green Premium product

Green Premium product

Compliant - since 1426 - Schneider Electric declaration of conformity

Compliant - since 1426 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Available

Available

Contractual warranty

Warranty period

18 months
