

Product data sheet

Characteristics

ATER

CCT15494

Svjetlosna sklopka IC100kp+ 1C SMART



Main

Range of product	Acti 9
Product name	Acti 9 IC
Product or component type	Programmable twilight switch with time switch function
Device short name	IC100kp+
Device application	Building
Provided equipment	Twilight sensor outdoor
Load type	Incandescent lamp 2600 W Halogen lamp 2600 W Non-corrected fluorescent tube 2300 VA Serial-compensated fluorescent tube 2300 VA Parallel compensated fluorescent lamp 730 VA 80 µF) Compact fluorescent lamp 170 W < 2 W LED lamp 30 W > 2 W LED lamp 200 W
Language	English French Russian Spanish Italian Dutch Danish Croatian Hungarian Slovene Portuguese German Romanian Polish Swedish Norwegian Finnish Czech

Complementary

Number of channels	1
Maximum power consumption in W	0,8 W standby
[Ue] rated operational voltage	230 V AC +10 % -15 % 50/60 Hz
Maximum switching current	10 A - 250 V AC 0,6 16 A - 250 V AC 1
Minimum switching current	10 MA 230 V AC 100 mA 24 V AC/DC
Electrical insulation class	Class II
Output type	Dry contact
Accuracy	+/- 0.25 s/day 25 °C
Contacts type and composition	C/O
Maximum number of switchings	84
Function available	External input for override Holiday schedules Automatic winter/summer time changeover Time limited or permanent deactivation of on/off function Switch preselection
Control type	By brightness detection By time schedule

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Control button type	4 push-buttons
Display type	Backlit LCD
Information displayed	Operating time counter per channel) Time Day Output contact status Current program
Time delay range	0...59 min on) 0...59 min off)
Backup time	10 years
Type of setting	Weekly programming
Light intensity adjustment	1...99000 lux
Connections - terminals	2 x 0,5...2,5 mm ² screw terminals solid or flexible 1 x 2,5 mm ² screw terminals solid or flexible with sleeve
Mounting support	TH35 DIN rail EN 60715
Maksimalna visina	92,6 mm
Maksimalna širina	45 mm
Maksimalna dubina	66,7 mm
Neto težina	134 g
Overvoltage category	Class 3
Marking	CE

Environment

Ambient air temperature for operation	-25...55 °C
Ambient air temp for storage/transportation	-30...70 °C
Relative humidity	90 %, non-condensing
IP degree of protection	IP20
Standards	EN 60669-2-1

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Informacije O Kraju Vijeka Trajanja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.