

CCTDD20001

STD – DIN – prigušivač svjetla na daljinsko upravljanje – 400 W



Glavno

Range	Acti 9
Product name	Acti 9 STD
Product or component type	Remote control dimmer
Device short name	STD
Product compatibility	Power regulators designed
Function available	Automatic load type detection

Komplementarno

Device application	Building
Load type	Low voltage halogen lamp with conventional transformer, (40...400 W) Low voltage halogen lamp with electronic transformer, (40...400 W) Low voltage halogen lamp with toroidal transformer, (40...300 W) Motor, (40...200 W) Halogen lamp, (230 V) (AC) (40...400 W) Incandescent lamp, (230 V) (AC) (40...400 W)
Control type	Local control: push-button Remote control: push-button
Power consumption in VA	0.8 VA
Thermal losses	3 W
[Ue] rated operational voltage	230 V (+/- 10 %) AC, 50 Hz
Protection type	Electronic overload protection Electronic overvoltage protection Electronic over temperature protection Single shot thermal fuse
Mounting support	DIN rail
9 mm pitches	4
Connected auxiliaries	Maximum 25 auxiliary push-buttons without light indication, distance : < 50 m Maximum 5 auxiliary push-buttons with light indication, distance : < 50 m
Connections - terminals	Screw terminals, 2 cable(s) <= 4 mm ² top
Height	85 mm
Width	36 mm
Depth	62 mm
Product weight	80 g

Okolina

IP degree of protection	IP20
standards	EN 60669-2-1
directives	89/336/EEC - electromagnetic compatibility 73/23/EEC - low voltage directive
ambient air temperature for operation	0...70 °C
ambient air temperature for storage	0...60 °C

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0947 - Schneider Electric declaration of conformity	Compliant - since 0947 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Available

Available

Contractual warranty

Warranty period

18 months
