

## DF143NC

osigurač–rastavljač TeSys 3P N 50A – veličina osigurača 14 x 51 mm



### Glavno

Range	TeSys
Product name	TeSys DF
Product or component type	Fuse-disconnector
Device short name	DF14
Poles description	3P + N

### Komplementarno

Mounting support	Rail
Mounting position	Vertical +/- 23°
Control type	Toggle
[Ie] rated operational current	50 A for power circuit
[Uimp] rated impulse withstand voltage	8 kV
Fire resistance	960 °C conforming to IEC 60695-2-1
[Ipk] rated peak withstand current	15 kA with tubular links conforming to IEC 60269-1
Short-circuit withstand	120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3 80 kA 690 V conforming to IEC 60947-3
Fuse size	14 x 51 mm
Fuse type	AM GG
[Ui] rated insulation voltage	690 V for power circuit AC 690 V for power circuit DC
Connections - terminals	1 solid cable(s) 2.5...25 mm <sup>2</sup> on screw clamp terminals for power circuit 2 solid cable(s) 2.5...10 mm <sup>2</sup> on screw clamp terminals for power circuit 1 flexible cable(s) 2.5...25 mm <sup>2</sup> without cable end on screw clamp terminals for power circuit 2 flexible cable(s) 2.5...10 mm <sup>2</sup> without cable end on screw clamp terminals for power circuit 1 flexible cable(s) 2.5...25 mm <sup>2</sup> with cable end on screw clamp terminals for power circuit 2 flexible cable(s) 2.5...10 mm <sup>2</sup> with cable end on screw clamp terminals for power circuit
Tightening torque	3.5 N.m power circuit: on screw clamp terminals

### Okolina

standards	IEC 60947-3 UL 512 CSA C22.2 No 39
product certifications	UR
IP degree of protection	IP20 conforming to IEC 60529
protective treatment	TH
ambient air temperature for storage	-40...80 °C
ambient air temperature for operation	-20...60 °C with derating
height	110.8 mm
width	105 mm
depth	76.5 mm
product weight	0.57 kg

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

### Offer Sustainability

---

Not Green Premium product	Not Green Premium product
Compliant - since 0701 - Schneider Electric declaration of conformity	Compliant - since 0701 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---