

DF222V

osigurač–rastavljač TeSys 2P 125A–vel.osigurača
22x58mm–indik. za pregor.osigur.



Glavno

| | |
|---------------------------|-------------------|
| Range | TeSys |
| Product name | TeSys DF |
| Product or component type | Fuse-disconnector |
| Device short name | DF22 |
| Poles description | 2P |

Komplementarno

| | |
|--|--|
| Mounting support | Rail |
| Mounting position | Vertical +/- 23° |
| Control type | Toggle |
| [Ie] rated operational current | 125 A for power circuit |
| [Uimp] rated impulse withstand voltage | 8 kV |
| Fire resistance | 960 °C conforming to IEC 60695-2-1 |
| [Ipk] rated peak withstand current | 19 kA with tubular links conforming to IEC 60269-1 |
| Short-circuit withstand | 120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3 80 kA 690 V conforming to IEC 60947-3 |
| Local signalling | Blown fuse indication |
| Fuse size | 22 x 58 mm |
| Fuse type | AM GG |
| [Ui] rated insulation voltage | 690 V for power circuit AC 690 V for power circuit DC |
| Connections - terminals | 1 solid cable(s) 2.5...35 mm ² on screw clamp terminals for power circuit 2 solid cable(s) 2.5...25 mm ² on screw clamp terminals for power circuit 1 flexible cable(s) 2.5...35 mm ² without cable end on screw clamp terminals for power circuit 2 flexible cable(s) 2.5...25 mm ² without cable end on screw clamp terminals for power circuit 1 flexible cable(s) 2.5...35 mm ² with cable end on screw clamp terminals for power circuit 2 flexible cable(s) 2.5...25 mm ² with cable end on screw clamp terminals for power circuit |
| Tightening torque | 4 N.m power circuit: on screw clamp terminals |
| Quantity per set | Set of 3 |

Okolina

| | |
|---------------------------------------|--|
| standards | IEC 60947-3 UL 512 CSA C22.2 No 39 |
| product certifications | UR |
| IP degree of protection | IP20 conforming to IEC 60529 |
| protective treatment | TH |
| ambient air temperature for storage | -40...80 °C |
| ambient air temperature for operation | -20...60 °C with derating |
| height | 127.5 mm |
| width | 70 mm |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

depth 76.5 mm

product weight 0.439 kg

Offer Sustainability

Not Green Premium product Not Green Premium product

Compliant - since 0701 - Schneider Electric declaration of conformity Compliant - since 0701 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period 18 months