



#### Main

Range	Asfora
Product or component type	Switch
Device presentation	Mechanism with fixing frame
Load type	Load for energy saving lamps with ballast 100 W
Colour tint	Aluminium
Type of packing	Flow-pack

#### Complementary

Device mounting	Flush
Switch function	Intermediate
Number of rocker	1
Power range	2300 W
Rated current	10 AX 250 V AC
Connections - terminals	Screwless terminals
Number of cables	2,0 2,5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13,0 mm
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Painted
Conductor material	Copper
Fixing mode	Screws or claws 51...70 mm
Maksimalna visina	71 mm
Maksimalna širina	71 mm
Maksimalna dubina	43,0 mm
Projecting depth	15 mm
Neto težina	0,0619 kg

#### Environment

Standards	IEC 60669-1
Product certifications	TSE VDE
Quality labels	CE UKR
IP degree of protection	IP20
Ambient air temperature for operation	-5...40 °C

## Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU RoHS	Sukladno <a href="#">Izjava EU RoHS</a>
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	<a href="#">Da</a>
Propis RoHS za Kinu	<a href="#">Izjava RoHS Za Kinu</a>
Izjava o očuvanju okoliša	<a href="#">Ekološki Profil Proizvoda</a>
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.