



Glavno

Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2P + E with shutters
Device presentation	Complete product
Socket additional information	Shuttered
Colour tint	White
Type of packing	Flow-pack

Komplementarno

Socket number	1
Device mounting	Flush
Power range	3680 W
Rated current	16 A 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 x 2.5 mm ²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13 mm
Material	ABS (acrylonitrile butadiene-styrene): cover frame ABS + PC : central plate
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...69 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	10 mm
Quantity per set	1
Product weight	0.081 kg

Okolina

standards	IEC 60884-1
product certifications	Aenor TSE VDE
IP degree of protection	IP20

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

