



**Glavno**

Range	Asfora
Product or component type	Single data outlet
Device application	Communication
Device presentation	Complete product
Cable shielding type	UTP
Data socket type	RJ45
Colour tint	White
Type of packing	Flow-pack

**Komplementarno**

Device mounting	Flush
Socket number	1
Communication network category	6
Connections - terminals	IDC
Number of cables	1
Cable stiffness	Rigid
Material	Cover frame: ABS (acrylonitrile butadiene-styrene) Central plate: ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws 51...80 mm
Height	83 mm
Width	83 mm
Depth	48 mm
Projecting depth	9 mm
Product weight	0.063 kg

**Okolina**

IP degree of protection	IP20
-------------------------	------

**Offer Sustainability**

Not Green Premium product	Not Green Premium product
Compliant - since 1352 - Schneider Electric declaration of conformity	Compliant - since 1352 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.