

EPH9900171

Asfora - dvostruka utičnica s bočnim uzemljenjem, antracit



Main

Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2 x 2P + E
Device presentation	Complete product
Colour tint	Anthracite
Type of packing	Flow-pack

Complementary

Socket number	2
Device mounting	Flush
Power range	3680 W
Rated current	16 A 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 2,5 mm ²
Cable stiffness	Flexible Solid stranded Rigid
Wire stripping length	11 mm
Material	ABS (acrylonitrile butadiene-styrene) cover frame ASA + PC central plate
Surface finish	Painted
Conductor material	Copper
Fixing mode	Claws 54...72 mm
Maksimalna visina	123 mm
Maksimalna širina	83 mm
Maksimalna dubina	46 mm
Projecting depth	23 mm
Quantity per set	1

Environment

Standards	IEC 60884-1
Product certifications	AENOR VDE UKR
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda