

ETK10134E

Ultra – vod ožičenja – 101 x 34 mm – plastični – bijeli
– 2 m



Glavno

Product or component type	Installation trunking
Colour tint	White - RAL 9010
Quantity per set	24 m
Type of packing	Protective foil

Komplementarno

Compartment partitioning	1 compartment
Trunking dimension	101 x 34 mm
Device composition	Front cover Trunking base
Trunking material	Plastic
Front opening size	75 mm
Fixing mode	Screw-fixed Pre-punched fixing hole with distance of 230 mm between centers
Material	PVC (polyvinyl chloride)
Length	2000 mm
Height	101 mm
Width	34 mm

Okolina

ambient air temperature for operation	-5...60 °C
environmental health and issues	Cadmium free Lead free
IP degree of protection	IP40
IK degree of protection	IK07
standards	EN 50085-1: 2005 EN 50085-2-1: 2006

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1826 - Schneider Electric declaration of conformity	Compliant - since 1826 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.