



## Glavno

Product or component type	Mini trunking
Colour tint	White RAL 9010
Quantity per set	224 m

## Komplementarno

Trunking material	Plastic
Compartment partitioning	1 compartment
Trunking dimension	12 x 12 mm
Fixing mode	Power cable: screw-fixed Pre-punched fixing hole with distance of 230 mm between centers
Material	PVC (polyvinyl chloride)
Length	2000 mm
Height	12 mm
Width	12 mm

## Okolina

IP degree of protection	IP40
IK degree of protection	IK07
ambient air temperature for operation	-5...60 °C
environmental health and issues	Cadmium free Lead free
product certifications	Low voltage directive 2006/95/EC
standards	EN 50085-1: 2005 EN 50085-2-1: 2006

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1826 - Schneider Electric declaration of conformity	Compliant - since 1826 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.