



Glavno

Range of product	Ultra
Product or component type	T-piece
Device application	Cable distribution
Colour tint	White RAL 9010
Quantity per set	Set of 40

Komplementarno

Trunking dimension	25 x 16 mm 25 x 25 mm
Trunking material	Plastic
Fixing mode	Snap-fitted
Material	ABS thermoplastic enclosure
Height	45 mm
Width	65 mm
Depth	27 mm

Okolina

environmental characteristic	Halogen free
standards	EN 50085-1: 2005 EN 50085-2-1: 2006
ambient air temperature for operation	-5...60 °C
IP degree of protection	IP40
IK degree of protection	IK07

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1826 - Schneider Electric declaration of conformity	Compliant - since 1826 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.