



Glavno

| | |
|---------------------------|--------------------------|
| Range of product | Ultra |
| Product or component type | Joint cover piece |
| Device application | Wiring device adaptation |
| Colour tint | White RAL 9010 |
| Quantity per set | Set of 20 |

Komplementarno

| | |
|--------------------|-----------------------------|
| Trunking dimension | 60 x 21 mm |
| Trunking material | Plastic |
| Fixing mode | Snap-fitted |
| Material | ABS thermoplastic enclosure |
| Length | 62.2 mm |
| Height | 23 mm |
| Width | 16 mm |

Okolina

| | |
|---------------------------------------|--|
| environmental characteristic | Halogen free |
| standards | EN 50085-1: 2005 EN 50085-2-1: 2006 |
| ambient air temperature for operation | -5...60 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1826 - Schneider Electric declaration of conformity | Compliant - since 1826 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.