

## ISM10150

OptiLine 45 – ožičenje instalacije 75 x 55 mm –  
aluminij – prirodno – 2000 mm



### Glavno

Range of product	OptiLine 45
Cabling installation system	Trunking
Product or component type	Installation trunking
Colour tint	Natural
Quantity per set	12 m
Market segment	Residential Small commercial

### Komplementarno

Trunking material	Aluminium
Trunking dimension	75 x 55 mm
Compartment partitioning	1 compartment
Mounting location	Internal
Fixing mode	By screws
Front opening size	45 mm
Material	Aluminium anodized
Length	2000 mm
Height	75 mm
Width	55 mm

### Okolina

standards	73/23/EEC 93/68/EEC EN 50085-1 2005 EN 50085-2-1 2002
ambient air temperature for operation	-25...60 °C
IP degree of protection	IP30

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1826 - Schneider Electric declaration of conformity	Compliant - since 1826 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.