



Glavno

Cabling installation system	Pole Post Trunking
Product or component type	Front cover

Komplementarno

Type of pole	One-sided Two-sided
Type of post	One-sided Two-sided
Colour tint	Natural
Quantity per set	24 m
Trunking material	Aluminium
Trunking dimension	120 x 55 mm 155 x 55 mm 185 x 55 mm 80 x 55 mm 95 x 55 mm
Pole/post surface finish	Anodized
Pole fixing mode	Free-standing Tension-mounted
Fixing mode	Snap-fitted
Material	Aluminium-anodized
Length	2000 mm
Height	71 mm
Width	13 mm
Market segment	Residential Small commercial

Okolina

standards	Conforming to 73/23/EEC Conforming to 93/68/EEC Conforming to EN 50085-1[Sapce]: 2005 Conforming to EN 50085-2-1[Sapce]: 2002 Conforming to NF C 68-102
ambient air temperature for operation	-25...60 °C
IP degree of protection	IP40

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1826 - Schneider Electric declaration of conformity	Compliant - since 1826 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
