

KBA40DF405TW

Canalis–Duž fleksibilnog dijela–40 A–0,5 m–
Kompatibilno s DALI-jem–bijela



Glavno

| | |
|--------------------------------|-----------------|
| Range of product | Canalis |
| Product or component type | Busbar trunking |
| Busbar description | Flexible length |
| Product compatibility | KBA |
| Direction change type | 3 dimensions |
| [Ie] rated operational current | 40 A at 35 °C |

Komplementarno

| | |
|--|---|
| Device application | Lighting Power socket distribution |
| Thermal stress limit | 900 kA ² .s |
| Radiated magnetic field | 2 pT |
| [Ue] rated operational voltage | 230...400 V |
| [Uimp] rated impulse withstand voltage | 4 kV |
| [Ui] rated insulation voltage | 690 V |
| [Icw] rated short-time withstand current | 0.94 kA |
| [Ipk] rated peak withstand current | 9.6 kA |
| THDI | 40 A at 0...15 % 32 A at 15...33 % 28 A at 33...100 % |
| Network frequency | 50/60 Hz |
| Control type | Communicating |
| Number of circuits | 1 |
| Mounting mode | By clips |
| Standards | IEC 60439-2 IEC 61439-6 |
| Width | 540 mm |
| Depth | 30 mm |
| Height | 46 mm |
| Length | 0.5 m |
| Colour | RAL 9003: white |
| Product weight | 50 g |

Okolina

| | |
|---------------------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK06 conforming to IEC 62262 |
| ambient air temperature for operation | 0...35 °C without derating |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 0940 - Schneider Electric declaration of conformity | Compliant - since 0940 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|---------------------------------------|---------------------------------------|
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
