

KBB25ED44305TW

Canalis–Duž ravnog dijela–25 A–3 m–2 kruga–
3L+N+PE–kompat. s DALI-jem–bijela



Glavno

| | |
|---------------------------|-----------------|
| Range of product | Canalis |
| Product or component type | Busbar trunking |
| Product compatibility | KBB |

Komplementarno

| | |
|--|--|
| Device application | Lighting Power socket distribution |
| Radiated magnetic field | 2 pT |
| [Ue] rated operational voltage | 230...400 V |
| [Uimp] rated impulse withstand voltage | 4 kV |
| [Ui] rated insulation voltage | 690 V |
| [Ie] rated operational current | 25 A at 35 °C |
| Network frequency | 50/60 Hz |
| [Icw] rated short-time withstand current | 0.44 kA |
| [Ipk] rated peak withstand current | 4.4 kA |
| Thermal stress limit | 195 kA ² .s |
| THDI | 25 A at 0...15 % 20 A at 15...33 % 16 A at 33...100 % |
| Voltage drop | 0.72 V with power factor = 1 at 50 Hz with 1A for 100 m long 0.67 V with power factor = 0.9 at 50 Hz with 1A for 100 m long 0.61 V with power factor = 0.8 at 50 Hz with 1A for 100 m long 0.55 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode | By screws |
| Busbar description | Straight length |
| Busbar trunking polarity | 3L + N + PE |
| Number of circuits | 2 |
| Number of tap-off outlets | 5 |
| Control type | Communicating |
| Standards | EN/IEC 60439-2 EN/IEC 61439-6 |
| Width | 3100 mm |
| Depth | 51 mm |
| Height | 60 mm |
| Length | 3 m |
| Colour | RAL 9003: white |
| Product weight | 4.8 kg |
| Quantity per set | Set of 6 |

Okolina

| | |
|-------------------------|---------------------------------|
| IP degree of protection | IP55 conforming to EN/IEC 60529 |
|-------------------------|---------------------------------|

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|---------------------------------------|--|
| IK degree of protection | IK06 conforming to EN/IEC 62262 |
| ambient air temperature for operation | 0...35 °C at 100 % of In 35...40 °C at 96 % of In 40...45 °C at 93 % of In 45...50 °C at 89 % of In 50...55 °C at 85 % of In |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1012 - Schneider Electric declaration of conformity | Compliant - since 1012 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|