

## KBC10DCB20

Canalis – razvodna jedinica – 10 A – odabir faze –  
bez zaštite – L+N+PE



### Glavno

Range	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBA KBB KDP
Device application	Lighting
Range compatibility	Canalis KBA Canalis KBB Canalis KDP

### Komplementarno

[Ue] rated operational voltage	230...240 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	10 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Busbar trunking polarity	L1 + N + PE L2 + L1 + L3 + PE L2 + N2 + L3 + PE
Tap-off unit polarity	L1+L2 L1+L3 L1+N L2+L3 L2+N L2+N2 L3+N L3+N3
Tap-off unit connector type	With phase selection
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	1 m
Depth	62 mm
Height	60 mm
Colour	RAL 9001 : cream
Product weight	65 g
Quantity per set	Set of 10

### Okolina

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0801 - Schneider Electric declaration of conformity	Compliant - since 0801 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------